

Flatwork dryer-ironers C140-160-200/32



Flatwork dryer-ironers

Front-service type to be used by one or two operators, with possibility of approaching the rotary drying press to the wall.

Perfect ironing and drying thanks to NOMEX® belts winding on nearly the whole roller surface.

Easy loading of laundry thanks to the laundry conveying strips allowing easy handling of the appliance.

Effective width 140 ÷ 160 ÷ 200cm.

Digital thermostat to select different temperatures and constant visual control of the attained temperature.

Safety thermostat to avoid undesirable overheating.

Adjustable roller revolving speed from 0.1m/min till 9m/min through frequency controlled motor.

Finger-saving fillet to protect the operator in case of wrong operation.

Manual device to move the roller and to take off the laundry in case of power failure.

Electronic device to start and to control the gas flame;

Chrome plated cylinder on request;

Warning: do not use gas drying-ironers in rooms where perchlore is used.

Flatwork dryer-ironers C140-160-200/32



ST23

ST23 control, standard on the entire gamma, manages temperature using the P.I.D. system (Proportional - Integral - Derivative).

Models C/32		140	160	200
Usable length	m	1.4	1.6	2.0
Cylinder diameter	cm	32.5	32.5	32.5
Moisture exhaust	number	1	1	2
Moisture exhaust diameter	mm	98	98	98
Extraction power	m ³ /h	500	500	1000
Heated surface	m ²	1.42	1.63	2.04
Capacity	kg/h	10 ÷ 20	20 ÷ 30	30 ÷ 40
Water evaporation	l/h	7 ÷ 14	14 ÷ 21	21 ÷ 28
Noise level	dB	60	60	63
ELECTRIC Heating				
Heating power	kW	12	16	21
Motor power	kW	0.37	0.37	0.49
Fuses	A	20 ÷ 32	25 ÷ 50	32 ÷ 63
Voltage supply	V / Hz / Ph	230-240V 3~50Hz 380-415V 3~ + N 50Hz		
GAS Heating				
Heating power	kW	14	22.5	30
Natural gas consumption	m ³ /h	1.5	2.4	3.2
Liquid gas consumption	kg/h	1.1	1.7	2.3
Motor power	kW	0.37	0.37	0.49
Fuses	A	2 ÷ 2	2 ÷ 2	2 ÷ 2
Voltage supply	V / Hz / Ph	230-240V 3~50Hz 380-415V 3~ + N 50Hz		
Net and shipping DIMENSIONS				
Floor space with trays	W ÷ D ÷ H (mm)	1960 ÷ 644 ÷ 1107	2210 ÷ 644 ÷ 1107	2560 ÷ 644 ÷ 1107
Shipping dimensions	W ÷ D ÷ H (mm)	2340 ÷ 770 ÷ 1400	2340 ÷ 770 ÷ 1400	2740 ÷ 770 ÷ 1400
Net and gross weight	kg	335 ÷ 355	375 ÷ 395	455 ÷ 475

C/32 201412 rel.01 The manufacturer declines all responsibility for any inaccuracies contained in this catalogue. The manufacturer reserves the right to bring, without warning, any modifications he might believe necessary, without changing the essential characteristics of the product.

