



Modular Cooking - Meritus 750 Electric Griddle Pan

NEGP 8-75 MR



*Due to routine technical improvement, the photograph shown may not represent the latest design of the products.

AVAILABLE MODEL

1. NEGP 8-75 MR

DESCRIPTION

Electric Griddle Pan with 9.2 kW power rate.

Water temperature maintained by thermostat with maximum working temperature of 300° C. Unit to be installed on open cabinet or similar elements, cantilever, or solid block solutions. Featuring removable clip joint to connect Meritus family product.

ITEM#	:
MODEL#	:
NAME	:

MAIN FEATURE

SN

- Maximum working temperature of 300°C.
- Unit to be installed free standing, can be joined wit base cabinet, table stand or cantilever system.
- Service maintenance can be done from the front pane

CONSTRUCTION

- All exterior panels in 304 type of Stainless Steel.
- Orbitel top panel anti-scratch finishing.
- Top and side are mounted by 1.5mm of Stainless Steel
- Adjustable ±25 mm Stainless Steel leg.
- Material Griddle is SS420 (t = 20mm).

INCLUDED ACCESSORIES

- Food Pan GN 1/1 x 100
- Nylon Drain Plug

OPTIONAL ACCESSORIES

Clip Plate for Joining

APPROVAL



ELECTRIC

FRONT

(z)

TOP

Ш

(II)°

(II)°

Electrical rating (kW) 9.2 Element rating (kW) 9.2

Electrical supply voltage 400V 3N

Required electrical supply (amps): 16

KEY INFORMATION

Unit dimension (WxDxH) :800x750x850/867 mm

Cooking surface (WxD) 630 x 510 mm

Direct heat emission 3.04 kW

Latent heat emission 3.68 kW

5.41 kg/h Steam emission

50°C Min. working temperature

300°C Max. working temperature

30 L Capacity

Net weight

PACKING DETAILS


Shipping width

Shipping depth

Shipping height

Shipping volume

Gross weight



127.5 Electric Connection * Overall Dimension in mm

APPROVAL