



Modular Cooking - Oriental **Gas Wok Table Top**

NGTL 6-65 SO



*Due to routine technical improvement, the photograph shown may not represent the latest design of the products.

AVAILABLE MODEL

1. NGTL 6-65 SO

DESCRIPTION

Gas Stock Pot with Powerful 28 kW Gas Burner. Can be used as Wok Range by mounting an adapter on the cast iron griddle. Designed to be a portable appliance inside an Oriental Kitchen. Top panel is constructed from a complete one piece of cast iron pot holder. Able to be used as wok ranges by attaching wok ring adaptor. The outer front casing is made from thick stainless steel to ensure longer lifetime of the appliance.

ITEM#	:
MODEL#	:
NAME	:

MAIN FEATURE

SN

- Gas Setting LNG or LPG.
- Gas Safety Flame Failure Device.
- Unit is potable model.
- Diameter Pot Maximal 500 mm.
- Cast iron griddle for Pot made sure to more stable.

CONSTRUCTION

All exterior panels is constructed of Stainless Steel.

INCLUDED ACCESSORIES

- Extra nozzle (Main burner & pilot burner).
- Ignition hand lighter.

OPTIONAL ACCESSORIES

N/A

APPROVAL

PT. NAYATI INDONESIA www.nayati.com nayati@nayati.com

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing. 2019.01.10

FRONT

GAS

Gas Consumption (G30) 28 kW

(24,000 kCal/h)

Gas Type Option G30/G31, G20

Gas Connection

LPG Gas Pressure G20:20 mbar

G25: 20-25 mbar

G30/31: 28-30 mbar

G30/31:50 mbar

KEY INFORMATION

Unit dimension (WxDxH) : 660x650x355/461 mm

Cooking Surface Wok Ø 400 mm

Direct heat emission 7.00 kW

Latent heat emission 4.20 kW

Steam emission (G30) 7.40 kg/h

Net weight 52 kg

PACKING DETAILS

SIDE


Shipping width 670 mm

730 mm Shipping depth

Shipping height 650 mm

0.317 m³ Shipping volume

Gross weight 62 kg



600 650

461 500 G

- Safety Knob
- Pilot Gas Valve
- Gas Valve Handle
- Gas Connection R 3/4"
 - * Overall Dimension in mm

APPROVAL