

Modular Cooking - Meritus

Gas - Range

NGTR 12-75 (ME1)



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Modular gas open burner with 750 mm depth and 6 hobs, 3 sets of 3.5 kW and 7.5 kW cast iron burners.

Usable for boiling, steaming, frying, braising, simmering and steam frying.

Made of AISI 304 with 1.5 mm top thickness, manual ignited, fully welded basin for hygiene purpose, galvanized coated cast iron burner.

OTHER AVAILABLE MODELS

NGR 8-75 (ME)

NGR 12-75 (ME)

NGTR 4-75 (ME)

NGTR 8-75 (ME)

NGR 8-75 EOVS (ME)

NGR 12-75 EOVS (ME)

MAIN FEATURES

- Powered with a 6 hobs, 3 sets of 3.5 kW and 7.5 kW cast iron open burner.
- Fully-welded basin for hygiene.
- Cast iron pot holder with long fin to support various size of pot or pan.
- Equipped with flame failure device.
- The optimized pan diameter for 3.5 kW burner is between 240-380 mm.
- The optimized pan diameter for 7.5 kW burner is between 300-500 mm.

CONSTRUCTION

- External construction entirely with AISI 304.
- Top panel with 1.5 mm thickness. Orbital surface finishing: resistant toward scratches.
- Front panel is constructed of 0.8 mm AISI 304 with satin surface finish.
- Side panel is constructed of 0.8 mm AISI 304 with satin surface finish.
- Tubular, height adjustable (-3...+50 mm) stainless steel legs.
- Nayati connection system between Meritus products on the top panels and cabinets.
- Cabinet executed with H2 radius.
- Deep drawn front panel to minimize liquid penetration to the internal part.
- Gasket protection behind the knobs to prevent water to seeping in, prolonging main heating regulation parts.


INCLUDED ACCESSORIES

- G20 Conversion Kit.
- Cast iron pot holder.
- Joint clip ME1.


OPTIONAL ACCESSORIES

- Stainless steel pot holder ME1.
- Swing door 12-75 ME1.


FRONT



TOP



SIDE



*Overall dimension in mm

TECHNICAL DATA

External Dimensions

Width	: 1200 mm
Depth	: 750 mm
Height	: 850/870 mm

Cooking Surface

Cooking zones	: 3 x 305 x 620 mm
---------------	--------------------

Gas Power Rating

Heat input total	: LPG/Natural Gas 33 kW
No. of burners	: 6
Control type	: High - low power control
Gas type options	: LPG G30, G31 Natural Gas G20, G25

Connections

Gas	: DN 20 (3/4")
Water	: N/A
Drain	: N/A

Heat & Steam Emissions

Direct heat emission	: 8.25 kW
Latent heat emission	: 3.3 kW
Steam emission	: 4.85 kg/h

PACKAGING DATA

Width	: 1230 mm
Depth	: 780 mm
Height	: 1020 mm
Volume	: 0.98 m ³

WEIGHT

Net Weight	: 102 kg
Gross Weight	: 128 kg

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.

12/12/2024