




Plus 20

N.1 TROLLEY 20 TRAYS GN 1/1
N.1 TROLLEY 20 TRAYS EN 60x40





External dimensions	1210 x 1085 x 2395 mm
Blast chilling (+90 °C, +3 °C)	100 kg
Shock freezing (+90 °C, -18 °C)	78 kg
Power supply	3 + N / 400 / 50

TECHNOLOGIES

-  NORTECH PLUS APP AND TOUCH-SCREEN 7"
-  COOKBOOK
-  HOT AND COLD CYCLES
-  HEATED CORE PROBE
-  HUMIDITY CONTROL (optional with ultrasonic moisture generator).
-  OZONE SANITIZING
-  SAVING HACCP DATA (Wi-Fi and USB connection for download and upload).

APPLICATIONS

-  BLAST CHILLING AND SHOCK FREEZING
-  LOW TEMPERATURE COOKING
-  READY DISH: THE RETHERM
-  FISH SANITIZING
-  ICE CREAM
-  PASTRY
-  PROOFING AND PROOFER RETARDER (optional with humidity generator)

CONSTRUCTION FEATURES

- Adaptive 7" touch screen controller
- Monocoque construction.
- Internal and external construction in AISI 304 stainless steel.
- Roll-in type blast chiller with ramp for the insertion of trolleys for GN 1/1 or EN 60x40 trays.
- Door gasket resistant to maximum and minimum temperatures.
- Cabinet profiles and door profiles resistant to maximum and minimum temperatures.
- Technical compartment placed above the cabinet.
- Condensing unit placed in the technical compartment, removable and easily inspectable from the back.
- Electrical panel placed in the compartment behind the controller, easy to be inspected.
- Internal cell with rounded corners to facilitate cleaning operations.
- CFC-free high density polyurethane insulation.
- Evaporator with cataphoresis rust protection.
- Left side door hinge.
- Core probes installed on the door.
- Heated door perimeter to avoid frost formation.
- Hot gas defrosting.

FUNCTIONS

- Probe cycles: the core probe temperature controls the cycle ensuring control and precision.
- Time cycles: the set duration controls the cycle.
- Timer cycles: 6 different timers can be set that automatically warn when the set duration is reached.
- Cascade cycles with multiple probes installed: the cycle allows to set a different target temperature for each installed core probe.
- Cascade cycles with one probe installed: this is a single-phase cycle with infinite time that allows different foodstuffs to be treated continuously without the need to act on the controller.
- Quick start: it is possible to choose a preferred cycle for quick start.

NORTECH PLUS APP

- User friendly controller
- Possibility to choose between factory preset cycles or to

- modify all the parameters of each cycle.
- Customizable multiphase cycles.
- Possibility to modify the parameters also during the current cycle.
- Rename of the display probes, to better distinguish the temperatures of each food.
- Graph of the temperatures during the current cycles.
- Recipe book for saving your favorite cycles.
- HACCP data storage with the possibility of downloading via usb key.
- Any alarms described on the display.

PROGRAMS

- Blast chilling and Shock freezing.
- Low temperature cooking
- Retherm.
- Proofing and proofer retarder (optional with humidity generator).
- Automatic sanitizing of fish.
- Ice cream hardening.
- Thawing.
- Bottle cooling.
- Hot gas defrosting.
- Cabinet drying.
- Pre-cooling.
- Pre-heating.
- Ozone cabinet sanitizing.

STANDARD EQUIPMENT

- n° 1 multi-point core probe.
- Ozone generator for cabinet sanitization cycles.
- Air cooled condensing unit.
- External condensate drain.

OPTIONAL EQUIPMENT

- Humidity generator.
- Predisposition for 4 core probes (1 probe included).
- Additional core probe.
- Condensate collection tray, located at the bottom of the evaporator inside the cell.
- Water cooled condensing unit.

Technical data	
Cooling capacity	9,23 Kw - (Evap. -10°C / Cond. 45°C)
Condensation	Air
Refrigerant gas	R404A - R452A
Ph / Volts / Hz	3 + N / 400 / 50
Max. power consumption cold cycles	6,40 Kw
Max. power consumption hot cycles	6,55 Kw (8,58 Kw optional humidity)
Trays and grids capacity	n° 1 trolley for 20 trays GN 1/1 n° 1 trolley for 20 trays EN 60x40
Blast chilling (+90 °C, +3 °C)	100 kg
Shock freezing (+90 °C, -18 °C)	78 kg
Internal dimensions	686 x 870 x 1880 mm
External dimensions	1210 x 1085 x 2395 mm
Packaging dimensions	1100 x 1230 x 2541 mm
Gross weight	410 kg
Net weight	370 kg

